



CONSUMER PRODUCTS SERVICES DIVISION

GUANGDONG XINYU TECHNOLOGY INDUSTRIAL CO., LTD

Technical Report: (8518)089-0921

Date Received: April 16, 2018

April 25, 2018

Page 1 of 5

GUANG DONG XIN YU TECHNOLOGY INDUSTRIAL CO LTD
LAIMEI INDUSTRIAL ZONE
CHENGHAI DISTRICT
SHANTOU, 515800
GUANGDONG, CHINA

Sample Description: RC TOYS

1.) A
2.) B
3.) C
4.) D
5.) E
6.) F

Vendor: N/A
Manufacturer: N/A

Sample Size: 6
Style No(s): XQRC32-
11AAA(3739) 、
XQRC32-
10AAA(3738/3165) 、
3433(3740) 、 3712 、
3813 、 3713

Buyer: N/A
Labeled Age Grade: AGES 8+
Appropriate Age Grade: NOT REQUESTED
Client Specified Age Grade: 3+

SKN/SKU No.: N/A
PO No.: N/A
Ref #: N/A
Country of Origin: CHINA

Tested Age Grade: OVER 3 YEARS OF AGE
UPC Code: 4895181837394, 4895181837387,
4895181837400, 4895181837127,
4895181838131, 4895181837134

Assortment No.: N/A
Country of Destination: EUROPEA

Test Starting Date: APRIL 16, 2018

Terminal voltage: 2 X 1.5V
3 X 1.5V

Test Finished Date: APRIL 25, 2018



GUANGDONG XINYU TECHNOLOGY INDUSTRIAL CO., LTD

Technical Report: **(8518)089-0921**

April 25, 2018

Page 2 of 5

EXECUTIVE SUMMARY:

The sample(s) MEET the following requirement(s):

- The requirements of the tested clauses of the European Standard EN 62115: 2005 + A2: 2011 + A11: 2012 + A12: 2015, "Electric toys - Safety"

Compliance with this standard is also on condition that the toy complies with EN71 Standard

Note: The submitted sample incorporating lasers or light emitting diodes (LED), compliance with the standard covered by this report is on condition that the lasers or light emitting diodes in toys are classified as Class 1 in accordance with IEC 60825-1 Standard under the condition specified in Annex E of EN 62115 / IEC 62115.

Note: Components shall comply with the safety requirements specified in the relevant IEC standards as far as they reasonably apply as specified in clause 16.1

BUREAU VERITAS SHENZHEN CO., LTD.

Lung Cheong Ming, Nick
Assistant Manager
Electrical Department
Toys, Premiums & Juvenile Products Division

NL/ah

This report shall not be reproduced except in full, without the written approval of our laboratory.



GUANGDONG XINYU TECHNOLOGY INDUSTRIAL CO., LTD

Technical Report: **(8518)089-0921**

April 25, 2018

Page 3 of 5

RESULTS:

European Standard EN 62115: 2005 + A2: 2011 + A11: 2012 + A12: 2015, "Electric toys - Safety"

Clause	Parameter	Result
5.13	Electrical connection can be made as reversed polarity due to incorrect insertion.	NOT POSSIBLE
7	Marking and Instructions	M
8	Power input	NA
9	Heating and abnormal operation	M-See Remark
10	Electric strength at operating temperature	M
11	Moisture resistance	M
12	Electric strength at room temperature	M
13	Mechanical strength	M
14	Construction	M
15	Protection of cords and wires	M
16	Components	M-See Executive Summary
17	Screws and connections	M
18	Creepage distance and clearances	M
19	Resistance to heat and fire	M
20	Radiation, toxicity and similar hazards	See Executive Summary
Annex ZB	Toys with protective electronic circuit	NA
Annex ZC	Toys generating Electromagnetic Fields (EMF)	NA

M = Meet

NA = Not applicable

NM/R = Not Meet-refer to Comment Section

NR = Not requested by the client



GUANGDONG XINYU TECHNOLOGY INDUSTRIAL CO., LTD

Technical Report: **(8518)089-0921**

April 25, 2018

Page 4 of 5

RESULTS:

Remark:

Clause	Parameter												
9.3	<p>The maximum temperature rises at normal operation were recorded as follows:</p> <p>Ambient Temperature (°C): 22.9</p> <table><tr><th><u>Location</u></th><th><u>Temperature Rise (K)</u></th><th><u>Limit (K)</u></th></tr><tr><td>Battery Surface (RX)</td><td>17.9</td><td>45</td></tr><tr><td>Enclosure (near motor) (RX)</td><td>17.3</td><td>50</td></tr><tr><td>Battery Surface (TX)</td><td>0.9</td><td>45</td></tr></table>	<u>Location</u>	<u>Temperature Rise (K)</u>	<u>Limit (K)</u>	Battery Surface (RX)	17.9	45	Enclosure (near motor) (RX)	17.3	50	Battery Surface (TX)	0.9	45
<u>Location</u>	<u>Temperature Rise (K)</u>	<u>Limit (K)</u>											
Battery Surface (RX)	17.9	45											
Enclosure (near motor) (RX)	17.3	50											
Battery Surface (TX)	0.9	45											
9.6	<p>The maximum temperature rises at locking motor condition were recorded as follows:</p> <p>Ambient Temperature (°C): 22.8</p> <table><tr><th><u>Location</u></th><th><u>Temperature Rise (K)</u></th><th><u>Limit (K)</u></th></tr><tr><td>Battery Surface(RX)</td><td>0.5</td><td>45</td></tr><tr><td>Enclosure (near motor) (RX)</td><td>0.7</td><td>50</td></tr><tr><td>Battery Surface (TX)</td><td>0.1</td><td>45</td></tr></table>	<u>Location</u>	<u>Temperature Rise (K)</u>	<u>Limit (K)</u>	Battery Surface(RX)	0.5	45	Enclosure (near motor) (RX)	0.7	50	Battery Surface (TX)	0.1	45
<u>Location</u>	<u>Temperature Rise (K)</u>	<u>Limit (K)</u>											
Battery Surface(RX)	0.5	45											
Enclosure (near motor) (RX)	0.7	50											
Battery Surface (TX)	0.1	45											

RESULTS:



Sample Number
85180890921A1



Sample Number
85180890921B1



Sample Number
85180890921C1



Sample Number
85180890921D1



Sample Number
85180890921E1



Sample Number
85180890921F1

END OF REPORT